

 **Harris**



 **BARRACUDA®**

What are the advantages?



Press Box Dimensions

60"W x 30"D x 92"L (152cm x 76cm x 234cm)

Charging Box Opening

56.75"W x 45"L (144cm x 114cm)

Hopper Opening

92"W x 54.75"L (manual feed) 234cm x 139cm)

Compression Chamber Size

60"W x 30"D x 40"L (152cm x 76cm x 102cm)

Approx. Expanded Bale Size

45"W x 30"D x 60"L (114cm x 76cm x 152cm)

Bale Volume

42 cubic feet (1.2 cubic m)

Approx. Expanded Bale Volume

47 cubic feet (1.3 cubic m)

Baling Cycle

Approx. 31 sec. dry cycle time (10" from floor)

Ram Face Pressure

117 PSI 10" from door (8 bars 25cm from door)

Electric Motors

One (1) 40 HP, 1750 RPM, 208/230/460v, 3 phase, 60 Hz
TEFC enclosure

Main Pump

One (1) 47 GPM, 5000 p.s.i. ((1) 178 LPM, 345 bars)

Cylinders

(2) 5.5" bore, 118 tons total ((2) 14cm bore, 107 tonne total)

Filtering

3 micron pressure filter

Shipping Weight

12.5 tons, approx. (11.3 tonnes, approx.)

Bale Weight (average)

Non-ferrous	1100-2000 lbs. (499-907 kg)
Steel Cans	1200-1300 lbs (544-590 kg)
Aluminum UBC	650-800 lbs. (295-363 kg)
OCC	1000-1200 lbs. (454-544 kg)
ONP	1200-1400 lbs. (544-635 kg)
Office	1200-1300 lbs. (544-590 kg)
Magazines	1600-2000 lbs. (726-907 kg)
PET	700-900 lbs. (318-408 kg)
HDPE	950-1050 lbs. (431-476 kg)

Performance rates, bale weights, and bale densities are subject to moisture content, material pre-bale densities, feed rates, and other variables.

7 7 0 . 6 3 1 . 7 2 9 0

www.harrisequip.com